## Boulevard TLI 150 Crescendo 125 Paver





|   | Colour                  |
|---|-------------------------|
|   |                         |
|   | White - Smooth          |
| = | Cinder Grey - Smooth    |
|   | Charcoal - Smooth       |
|   | Light Charcoal - Smooth |
|   | Black ETX - Smooth      |
|   | Light Grey - Smooth     |
|   | Beige Grey - Smooth     |
|   | Beige - Smooth          |
|   | Red - Smooth            |
|   |                         |

| _ 1 |     |
|-----|-----|
| 8   |     |
| Ě.  | 222 |
| Ψ   | ~~~ |
| ΞÛ. |     |

| Colour                     |
|----------------------------|
| Cinder Grey - Granitech    |
| Light Charcoal - Granitech |
| Charcoal - Granitech       |
| Light Grey - Granitech     |
| Beige Grey - Granitech     |
| Beige - Granitech          |
| Opal White - Granitech     |
| Stanstead Grey - Granitech |
| Cambrian Brown - Granitech |
| Cambrian Black - Granitech |
|                            |

|                 |                      | Dimensions mm      | Dimensions in.             |
|-----------------|----------------------|--------------------|----------------------------|
| A               | A                    | 150 x 125 x 333.33 | 5 7/8 x 4 15/16 x 13 1/8   |
| в               | В                    | 150 x 125 x 416.67 | 5 7/8 x 4 15/16 x 16 3/8   |
| E CONTRACTOR OF | С                    | 150 x 125 x 458.33 | 5 7/8 x 4 15/16 x 18       |
| c and           | D                    | 150 x 125 x 500    | 5 7/8 x 4 15/16 x 19 11/16 |
|                 | E                    | 150 x 125 x 541.67 | 5 7/8 x 4 15/16 x 21 5/16  |
| D               | F                    | 150 x 125 x 583.33 | 5 7/8 x 4 15/16 x 23       |
|                 | Cube ft <sup>2</sup> | 53.80              | 10.76 per row              |
| E               | Cube ft <sup>2</sup> | 53.80              | 10.76 per row              |
|                 | Cube ft <sup>2</sup> | 43.04              | 10.76 per row              |
| F               |                      |                    |                            |

| Mass/ft <sup>2</sup> | 32.6 kg | 71.7 lb |
|----------------------|---------|---------|
| Mass/ft <sup>2</sup> | 34.4 kg | 75.7 lb |
| Mass/ft <sup>2</sup> | 43.6 kg | 95.9 lb |

| Typical Row |
|-------------|
|-------------|



## Laying Pattern

smooth

| I |
|---|
| I |
| Т |
|   |

Linear

## TECHNICAL INFORMATION

| Product   | Standard   | Flexural Strength | Compressive<br>Strength | De-icing salts freeze-thaw durability                | Density | Absorption | Dimension Tolerance*   |
|---|------------|-------------------|-------------------------|--|---------|------------|--|
| Boulevard TLI 150<br>Crescendo 125 Paver<br>125 x 333.33<br>125 x 416.67<br>125 x 458.33<br>125 x 500<br>125 x 541.67<br>125 x 583.33 | CSA A231.2 | N/A               | µ 50 MPa<br>≥ 45 MPa    | 225 g/m² after 28 cycles<br>500 g/m² after 49 cycles | N/A     | N/A        | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm |

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.