



# Boulevard TLI 150 Paver



smooth

[≡]

| Colour                  |
|-------------------------|
| White - Smooth          |
| Cinder Grey - Smooth    |
| Charcoal - Smooth       |
| Light Charcoal - Smooth |
| Black ETX - Smooth      |
| Light Grey - Smooth     |
| Beige Grey - Smooth     |
| Beige - Smooth          |
| Red - Smooth            |

| textured<br> | Colour                     |
|-----------------------------------------------------------------------------------------------|----------------------------|
|                                                                                               | Cinder Grey - Granitech    |
|                                                                                               | Light Charcoal - Granitech |
|                                                                                               | Charcoal - Granitech       |
|                                                                                               | Light Grey - Granitech     |
|                                                                                               | Beige Grey - Granitech     |
|                                                                                               | Beige - Granitech          |
|                                                                                               | Opal White - Granitech     |
|                                                                                               | Stanstead Grey - Granitech |
|                                                                                               | Cambrian Brown - Granitech |
| Cambrian Black - Granitech                                                                    |                            |


| 125 x 150            | Dimensions mm           | Dimensions in.                 |
|----------------------|-------------------------|--------------------------------|
| A                    | 150 x 500 x 125         | 5 7/8 x 19 11/16 x 4 15/16     |
| Unit/area            | 16 units/m <sup>2</sup> | 1.49 units/ft <sup>2</sup>     |
| Cube ft <sup>2</sup> | 60.55                   | 12.11 per row / 48.44 par cube |



|                      |         |         |
|----------------------|---------|---------|
| Mass/ft <sup>2</sup> | 32.6 kg | 71.7 lb |
| Mass/ft <sup>2</sup> | 34.4 kg | 75.7 lb |
| Mass/ft <sup>2</sup> | 43.6 kg | 95.9 lb |

Sold separately

Typical Row




| 250 x 500            | Dimensions mm          | Dimensions in.                 |
|----------------------|------------------------|--------------------------------|
| B                    | 150 x 500 x 250        | 5 7/8 x 19 11/16 x 9 7/8       |
| Unit/area            | 8 units/m <sup>2</sup> | 0.74 units/ft <sup>2</sup>     |
| Cube ft <sup>2</sup> | 67.25                  | 13.45 per row / 40.35 par cube |




|                      |         |         |
|----------------------|---------|---------|
| Mass/ft <sup>2</sup> | 32.6 kg | 71.7 lb |
| Mass/ft <sup>2</sup> | 34.4 kg | 75.7 lb |
| Mass/ft <sup>2</sup> | 43.6 kg | 95.9 lb |

Sold separately

Typical Row




| 500 x 500            | Dimensions mm          | Dimensions in.                 |
|----------------------|------------------------|--------------------------------|
| C                    | 150 x 500 x 500        | 5 7/8 x 19 11/16 x 19 11/16    |
| Unit/area            | 4 units/m <sup>2</sup> | 0.37 units/ft <sup>2</sup>     |
| Cube ft <sup>2</sup> | 64.56                  | 10.76 per row / 43.04 par cube |



|                      |         |         |
|----------------------|---------|---------|
| Mass/ft <sup>2</sup> | 32.6 kg | 71.7 lb |
| Mass/ft <sup>2</sup> | 34.4 kg | 75.7 lb |
| Mass/ft <sup>2</sup> | 43.6 kg | 95.9 lb |


Sold separately

Typical Row



# Boulevard TLI 150 Paver - cont'd

750 x 500




|                      | Dimensions mm             | Dimensions in.             |
|----------------------|---------------------------|----------------------------|
| D                    | 150 x 500 x 750           | 5 7/8 x 19 11/16 x 29 1/2  |
| Unit/area            | 2.67 units/m <sup>2</sup> | 0.25 units/ft <sup>2</sup> |
| Cube ft <sup>2</sup> | 48.42                     | 8.07 per row               |

|                      |         |         |
|----------------------|---------|---------|
| Mass/ft <sup>2</sup> | 32.6 kg | 71.7 lb |
| Mass/ft <sup>2</sup> | 34.4 kg | 75.7 lb |
| Mass/ft <sup>2</sup> | 43.6 kg | 95.9 lb |

Sold separately

Typical Row



200 x 200




|                      | Dimensions mm   | Dimensions in.        |
|----------------------|-----------------|-----------------------|
| E                    | 150 x 200 x 200 | 5 7/8 x 7 7/8 x 7 7/8 |
| Cube ft <sup>2</sup> | 51.6            | 8.6 per row           |


|                      |         |         |
|----------------------|---------|---------|
| Mass/ft <sup>2</sup> | 32.6 kg | 71.7 lb |
| Mass/ft <sup>2</sup> | 34.4 kg | 75.7 lb |
| Mass/ft <sup>2</sup> | 43.6 kg | 95.9 lb |

Sold separately


Typical Row




## Laying Patterns




Modular  
17% B + 33% C + 50% D




Modular  
21% B + 42% C + 37% D




Modular  
21% B + 17% C + 62% D




Modular  
25% B + 50% C + 25% D



Modular  
13% B + 25% C + 62% D



Modular  
8% B + 17% C + 75% D



Modular  
29% B + 33% C + 38% D

## TECHNICAL INFORMATION

| Product                        | Standard   | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability                                        | Density | Absorption | Dimension Tolerance*                                                 |
|--------------------------------|------------|-------------------|----------------------|------------------------------------------------------------------------------|---------|------------|----------------------------------------------------------------------|
| <b>Boulevard TLI 150 Paver</b> |            |                   |                      |                                                                              |         |            |                                                                      |
| 125 x 500                      |            |                   |                      |                                                                              |         |            |                                                                      |
| 250 x 500                      |            |                   |                      |                                                                              |         |            |                                                                      |
| 500 x 500                      | CSA A231.2 | N/A               | μ 50 MPa<br>≥ 45 MPa | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles | N/A     | N/A        | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm |
| 750 x 500                      |            |                   |                      |                                                                              |         |            |                                                                      |
| 200 x 200                      |            |                   |                      |                                                                              |         |            |                                                                      |

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.