




Capio Paver



		Dimensions mm		Dimensions in.	Code	Colour	Typical Row
A		A	60 x 152 x 102	2 3/8 x 6 x 4		Prestige	
		B	60 x 152 x 152	2 3/8 x 6 x 6	127001183	Range Amber Beige	
B		C	60 x 152 x 203	2 3/8 x 6 x 8	127001181	Range Scandina Grey	
		D	60 x 152 x 254	2 3/8 x 6 x 10	127001182	Rockland Black	
C		E	60 x 152 x 305	2 3/8 x 6 x 12		Standard	
		Weight/unit	4 kg	9 lb	127001983	Range Newport Grey - 97	
D		Unit/area (avg.)	0.03 unit/m²	0.33 unit/ft²	Production location Montreal and Quebec		
		Area/layer (avg.)	1.07 m²	11.5 ft²			
		Area/cube	10.7 m²	10 Rows	115 ft²		
E		Qty/cube	A=80 B=80 C=80 D=60 E=60				
		Weight/cube	1467 kg	3234 lb			

Laying Pattern



Linear

Techniseal 1 bag of sand covers approx. 108 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Capio Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.