

Celtik® Wall



textured



	Dimensions mm		Dimensions in.	
A	A	90 x 225 x 175	3 9/16 x 8 7/8 x 6 7/8	
B	B	90 x 225 x 265	3 9/16 x 8 7/8 x 10 7/16	
C	C	90 x 225 x 345	3 9/16 x 8 7/8 x 13 9/16	
D	D	90 x 225 x 435	3 9/16 x 8 7/8 x 17 1/8	
	Weight/unit (avg.)	14 kg	31 lb	
	Area/layer (1 to 6)	0.45 m ²	4.89 ft ²	
	Area/cube	3.18 m²	7 Rows	34.22 ft²
	Qty/cube	A = 28 B = 28	C = 28 D = 28	
	Length/row (1 to 6)	4.88 lin. m	16.00 lin. ft	
	Length/cube	34.14 lin. m	11.00 lin. ft	
	Weight/cube	1590 kg	3505 lb	


For each unit of 90 mm, 1 alignment pin is included

Note: 1/4 layer = 1.22 ft²


1/8 layer = 0.61 ft²

Code	Colour
16252364	Range Sheffield Beige & Black
16252362	Range Norvick Grey
Production location Trois-Rivières	

Typical Row



Laying Pattern



Linear

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Celtik Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ²	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

Applications: Retaining walls - steps

Recommended Capping units: Celtik Straight Capping unit

Additional details: See our landscaping installation guide on our website.