




Melville® 60 Small Rectangle Paver




		Dimensions mm	Dimensions in.	Code	Colour	Typical Row
		60 x 190 x 380	2 3/8 x 7 1/2 x 15		Prestige	
	Weight/unit	10 kg	22 lb	12053044	Range Amber Beige	
	Unit/area	13.89 units/m²	1.29 units/ft²	12052446	Rockland Black	
	Area/layer	0.87 m²	9.33 ft²	12052448	Range Scandina Grey	
	Area/cube	10.44 m²	12 Rows	111.96 ft²	Standard	
	Length/row	4.57 lin. m	15.00 lin. ft	12053043	Range Shaded Grey	
	Length/cube	54.86 lin. m	180.00 lin. ft	Can be double stacked Production location Montreal, Quebec and Metcalfe		
	Qty/cube	144 units	144 units			
	Weight/cube	1431 kg	3154 lb			

Laying Patterns



Linear



Herringbone

 1 bag of sand covers approx. 103 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 60 Small Rectangle Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. The Melville 60 Slab is compatible with the Melville 60 small rectangle paver for non-vehicular application only.