

Vendome® 60 and 80 Paver



60 mm		Dimensions mm	Dimensions in.
Not vehicular	A	60 x 130 x 197	2 3/8 x 5 1/8 x 7 3/4
	B	60 x 130 x 262	2 3/8 x 5 1/8 x 10 5/16
	C	60 x 130 x 327	2 3/8 x 5 1/8 x 12 7/8
A	Weight/unit (avg.)	4 kg	9 lb
	Unit/area (avg.)	30.50 units/m²	2.83 units/ft²
	Area/layer	1.05 m²	11.28 ft²
B	Area/cube	8.40 m²	8 Rows 90.24 ft²
	Length/row	8.19 lin. m	26.87 lin. ft
	Length/cube	65.52 lin. m	214.96 lin. ft
C	Weight/cube	1044 kg	2302 lb

80 mm		Dimensions mm		Dimensions in.
A 	A	80 x 130 x 197		3 1/8 x 5 1/8 x 7 3/4
	B	80 x 130 x 262		3 1/8 x 5 1/8 x 10 5/16
	C	80 x 130 x 327		3 1/8 x 5 1/8 x 12 7/8
	Weight/unit (avg.)	5 kg	12 lb	
B 	Unit/area (avg.)	30.50 units/m²		2.83 units/ft²
	Area/layer	1.05 m²		11.28 ft²
	Area/cube	8.40 m²	8 Rows	90.24 ft²
C 	Qty/cube	A = 88	B = 96	C = 72
	Length/row	7.86 lin. m		25.80 lin. ft
	Length/cube	62.90 lin. m		206.40 lin. ft
	Weight/cube	1382 kg		3047 lb

Code	Colour
	Prestige
10554763	Rockland Black
10554761	Range Margaux Beige
	Standard
10554762	Range Newport Grey
Production location Montreal	

Typical Row


A	A	A	A	A	A
C	C	B	B		
A	B	B	B	A	
C	C	B	B		
C	C	B	B		
C	C	B	B		
C	A	A	A	B	

Code	Colour
	Prestige
10550002	Rockland Black
10559011	Range Margaux Beige
	Standard
10559010	Range Newport Grey
Production location Montreal	


Typical Row

A	A	A	A	A	A
C	C	B	B		
A	B	B	B	A	
C	C	B	B		
C	C	B	B		
C	C	B	B		
C	A	A	A	B	

Laying Patterns



Linear



Modular

Techniseal 1 bag of sand covers approx. : Vendome 60 - 44 ft² / Vendome 80 - 33 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Vendome Paver	CSA A231.2	N/A	µ 50 MPa ≥ 45 MPa	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Runoff coefficient: 126 in per hour

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).