


	Metric (mm)	Imperial (in.)
	80 x 98 x 198	3 1/8 x 3 41/48 x 7
Weight/unit	3 kg	8 lb
Area/unit	0.42 m <sup>2</sup>	4.58 ft <sup>2</sup>
Area/cube	8.77 m <sup>2</sup>	94.40 ft <sup>2</sup>
Length/cube	132.60 lin. ft (rectangles only)	
Qty/cube	464 units (400 rectangles, 64 half-stone)	
Weight/cube	1608 kg	3545 lb

Code	Colour
10501969	Natural

Contact your sales representative for custom colours.

Packaged in herringbone to facilitate mechanical installation

### Laying Pattern



Herringbone



### Technical Information

Product	AquaPave Paver
Standard	CSA A231.2
Flexural Strength	N/A
Compressive Strength	μ 50 MPa ≥ 45 MPa
De-icing salts freeze-thaw durability	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint spacing is 6 mm (0.24 in.) which allows an initial surface infiltration rate of +/- 3 018 mm/hr.

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.