

# City Slab


	Metric (mm)	Imperial (in.)
	60 x 500 x 750	2 3/8 x 19 11/16 x 29 1/2
Weight/unit	52 kg	114 lb
Area/unit	0.38 m <sup>2</sup>	4.04 ft <sup>2</sup>
Area/layer	0.75 m <sup>2</sup>	8.07ft <sup>2</sup>
Area/cube	9.00 m <sup>2</sup> 12 Rows	96.84 ft <sup>2</sup>
Qty/cube	24 units	24 units
Weight/cube	1270 kg	2800 lb

Code	Colour
12059437	Alpine Grey
12059443	Sterling Grey


Production location Montreal

1 bag of Techniseal sand covers approx.: 231 ft<sup>2</sup>

## Typical Row



## Laying Pattern



Linear



## Technical Information

Product	City Slab
Standard	CSA A231.1
Flexural Strength	±4.5 MPa
Compressive Strength	N/A
De-icing salts freeze-thaw durability	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Given the weight of this slab, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation). This product can be installed on pedestals for a rooftop application. It can safely withstand a load of up to 300 kg.