




# Melia 6 x 6 DuraFusion Paver


	Metric (mm)	Imperial (in.)
	60 x 152 x 152	2 3/8 x 6 x 6
Weight/unit	3 kg	7 lb
Area/unit	0.02 m <sup>2</sup>	0.25 ft <sup>2</sup>
Area/layer	1.11 m <sup>2</sup>	12.0 ft <sup>2</sup>
Area/cube	11.15 m <sup>2</sup> 10 Rows	120.0 ft <sup>2</sup>
Qty/cube	480 units	480 units
Weight/cube	1521 kg	3354 lb

Code	Colour - DuraFusion	
127003277	Amber	 N
127002105	Marbella	
127002106	Hickory	


Production location Milton

1 bag of Techniseal sand covers approx.: 89 ft<sup>2</sup>


## Typical Row



## Laying Pattern



Checkerboard



Running Bond



## Technical Information

Product	Melia 6 x 6 DuraFusion Paver
Standard	CSA A231.2
Flexural Strength	N/A
Compressive Strength	μ 50 MPa ≥ 45 MPa
De-icing salts freeze-thaw durability	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.