



Cassara® Large Rectangle Slab

	Metric (mm)	Imperial (in.)
	60 x 300 x 700	2 3/8 x 11 13/16 x 27 9/16
Weight/unit	29 kg	64 lb
Area/unit	0.21 m ²	2.26 ft ²
Area/layer	0.63 m ²	6.78 ft ²
Area/cube	7.56 m ² 12 Rows	81.36 ft ²
Qty/cube	36 units	36 units
Weight/cube	1073 kg	2369 lb
Code		
Colour - Prestige		
10200759	Range Scandina Grey	
10200651	Range Amber Beige	
10200653	Rockland Black	
Colour - Standard		
10200652	Range Shaded Grey	
Production location	Montreal	
1 bag of Techniseal sand covers approx.: 162 ft ²		



Technical Information

Product	Cassara Large Rectangle Slab
Standard	CSA A231.1
Flexural Strength	±4.5 MPa
Compressive Strength	N/A
De-icing salts freeze-thaw durability	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cassara Large Rectangle Slabs are designed to be installed in a linear pattern with transversal joints staggered by at least 100 mm. Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.