Metrik™ Slab

	Metric (mm)	**Imperial** (in.)
	60 x 70 x 280	2 3/8 x 2 3/4 x 11
Weight/unit	3 kg	6 lb
Area/unit	0.02 m²	0.21 ft²
Area/layer	0.92 m²	9.95 ft²
Area/cube	11.09 m² 12 Rows	119.40 ft²
Qty/cube	576 units	576 units
Weight/cube	1505 kg	3319 lb

Code	**Colour - Prestige**
10502882	Rockland Black
127000940	Range Scandina Grey

Production location	Montreal
Can be double stacked	
Sold in full cubes	

1 bag of Techniseal sand covers approx.: 85 ft²

Typical Row



Laying Pattern



Checkerboard



Offset 1/2



Offset 1/3



Herringbone

Technical Information

Product	Metrik Slab
Standard	CSA A231.1
Flexural Strength	±4.5 MPa
Compressive Strength	N/A
De-icing salts freeze-thaw durability	225 g/m² after 28 cycles 500 g/m² after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.