

Mondrian® Plus 60 Slab


| | Metric (mm) | Imperial (in.) |
|--------------------|------------------------------|------------------------|
| A | 60 x 165 x 330 | 2 3/8 x 6 1/2 x 13 |
| B | 60 x 330 x 330 | 2 3/8 x 13 x 13 |
| C | 60 x 330 x 495 | 2 3/8 x 13 x 19 1/2 |
| Weight/unit (avg.) | 13 kg | 28 lb |
| Area/unit | 0.11 m ² | 1.17 ft ² |
| Area/layer | 0.98 m ² | 10.55 ft ² |
| Area/cube | 11.76 m ² 12 Rows | 126.60 ft ² |
| Qty/cube | A = 48 B = 48 C = 24 | |
| Weight/cube | 1551 kg | 3419 lb |

| Code | Colour - Prestige |
|-------------------|---------------------|
| 12052893 | Range Margaux Beige |
| 12052894 | Range Amboise Beige |
| 12052566 | Range Scandina Grey |
| Colour - Standard | |
| 12052891 | Range Norvick Grey |
| 12052892 | Range Newport Grey |


Production location Montreal, Quebec and Metcalfe
 Can be double stacked

1 bag of Techniseal sand covers approx.: 65 ft²


Typical Row



Laying Pattern



Linear
100% Mix A, B, C



Modular
100% Mix A, B, C



Technical Information

| | |
|---------------------------------------|--|
| Product | Mondrian Plus 60 Slab |
| Standard | CSA A231.1 |
| Flexural Strength | ±4.5 MPa |
| Compressive Strength | N/A |
| De-icing salts freeze-thaw durability | 225 g/m ² after 28 cycles 500 g/m ² after 49 cycles |
| Density | N/A |
| Absorption | N/A |
| Dimension Tolerance* | Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm |

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. The Mondrian Plus 60 Slab is compatible with the Mondrian Plus 60 Small Rectangle paver for non-vehicular application only.