

# Boulevard TLI 150 Paver



## Colour - Smooth


White - Smooth  
Cinder Grey - Smooth  
Charcoal - Smooth  
Black ETX - Smooth  
Light Grey - Smooth  
Beige Grey - Smooth  
Beige - Smooth  
Red - Smooth  
Brown - Smooth

## Colour - Textured

White - Granitech  
Cinder Grey - Granitech  
Charcoal - Granitech  
Black ETX - Granitech  
Light Grey - Granitech  
Beige Grey - Granitech  
Beige - Granitech  
Red - Granitech  
Brown - Granitech

200 x 200	Metric (mm)	Imperial (in.)
	150 x 200 x 200	5 7/8 x 7 7/8 x 7 7/8
Cube/ft <sup>3</sup>	51.6	8.6 per row
Mass/ft <sup>2</sup>	32.6 kg	71.7 lb
Sold separately		

## Typical Row



## Technical Information

Product	Boulevard TLI 150 Paver
Standard	CSA A231.2
Flexural Strength	N/A
Compressive Strength	μ 50 MPa ≥ 45 MPa
De-icing salts freeze-thaw durability	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.