

Kensington Paver

RECTANGLE	Metric (mm)	Imperial (in.)
	80 x 209 x 279	3 1/8 x 8 1/4 x 11
Weight/unit	10 kg	23 lb
Units/area	-	1.55 units/ft ²
Area/section	-	23.17 ft ²
Area/cube	-	92.70 ft ²
Length/section	-	25 lin. ft
Length/cube	-	100 lin. ft
Qty	144 units/cube	36 units/section
Weight	1498 kg	3304 lb

Code	Colour
10500847	Sierra Black

Production location	Milton
Sold in full cubes	



MIXED BUNDLE	Metric (mm)	Imperial (in.)
C	80 x 279 x 419	3 1/8 x 11 x 16 1/2
Weight/unit	21.36 kg	47.10 lb
Units/area	-	0.78 unit/ft ²
Qty/cube	36 units	36 units
B	80 x 279 x 279	3 1/8 x 11 x 11
Weight/unit	14.33 kg	31.60 lb
Units/area	-	1.17 units/ft ²
Qty/cube	36 units	36 units
A	80 x 139 x 279	3 1/8 x 5 1/2 x 11
Weight/unit	7.07 kg	15.60 lb
Units/area	-	2.32 units/ft ²
Qty/cube	36 units	36 units
Area/cube	-	92.43 ft ²
Weight/cube	1515 kg	3341 lb

Code	Colour
10500842	Canyon Grey Blend
10506472	Granite Blend


Production location	Milton
Sold in full cubes	

1 bag of Techniseal sand covers approx.: 37 ft²


Typical Row




Laying Pattern




Modular



Linear



Herringbone
100% Rectangle



Running Bond
100% Rectangle



Technical Information

Product	Kensington Paver
Standard	CSA A231.2
Flexural Strength	N/A
Compressive Strength	μ 50 MPa ≥ 45 MPa
De-icing salts freeze-thaw durability	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Runoff coefficient (mixed bundle): 247 in per hour



Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.