

## Leno Bullnose Capping [≡]

|             | Metric (mm)       | Imperial (in.)    |
|-------------|-------------------|-------------------|
|             | 60 x 305 x 915    | 2 3/8 x 12 x 36   |
| Weight/unit | 40 kg             | 88 lb             |
| Unit/area   | 3.58 units/lin. m | 0.33 unit/lin. ft |
| Length/row  | 10.98 lin. m      | 36 lin. ft        |
| Length/cube | 21.96 lin. m      | 72 lin. ft        |
| Qty/cube    | 24 units          | 2 Rows 24 units   |
| Weight/cube | 969 kg            | 2136 lb           |

| Code      | Colour              |
|-----------|---------------------|
| 121000280 | Range Amber Beige   |
| 121000278 | Range Shaded Grey   |
| 121000277 | Range Scandina Grey |
| 121000279 | Rockland Black      |

|                          |        |
|--------------------------|--------|
| Production location      | Québec |
| Cannot be double stacked |        |

### Typical Row

[illegible]

## Technical Information

|                                          |                                                      |
|------------------------------------------|------------------------------------------------------|
| Product                                  | Leno Bullnose Capping                                |
| Standard                                 | ASTM C 1372                                          |
| Flexural Strength                        | N/A                                                  |
| Compressive Strength                     | 20.7 MPa                                             |
| De-icing salts<br>freeze-thaw durability | N/A                                                  |
| Density                                  | 2000 kg/m <sup>2</sup>                               |
| Absorption                               | 10.4%                                                |
| Dimension<br>Tolerance*                  | Length: ±3.2 mm<br>Width: ±3.2 mm<br>Height: ±3.2 mm |

Additional details specific to this product are available by consulting our landscaping installation guide on our website.