

|             | Metric (mm)                  | Imperial (in.)         |
|-------------|------------------------------|------------------------|
|             | 60 x 70 x 280                | 2 3/8 x 2 3/4 x 11     |
| Weight/unit | 3 kg                         | 6 lb                   |
| Area/unit   | 0.02 m <sup>2</sup>          | 0.21 ft <sup>2</sup>   |
| Area/layer  | 0.92 m <sup>2</sup>          | 9.95 ft <sup>2</sup>   |
| Area/cube   | 11.09 m <sup>2</sup> 12 Rows | 119.40 ft <sup>2</sup> |
| Qty/cube    | 576 units                    | 576 units              |
| Weight/cube | 1505 kg                      | 3319 lb                |

| Code      | Colour - Prestige   |
|-----------|---------------------|
| 10502882  | Rockland Black      |
| 127000940 | Range Scandina Grey |





  

|                       |        |
|-----------------------|--------|
| Production location   | Milton |
| Can be double stacked |        |

1 bag of Techniseal sand covers approx.: 85 ft<sup>2</sup>

| Typical Row |  |  |  |
|-------------|--|--|--|
|             |  |  |  |
|             |  |  |  |
|             |  |  |  |
|             |  |  |  |
|             |  |  |  |
|             |  |  |  |
|             |  |  |  |
|             |  |  |  |
|             |  |  |  |
|             |  |  |  |
|             |  |  |  |

| Laying Pattern                                                                      |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |
| Checkerboard                                                                        | Offset 1/2                                                                          |
|  |  |
| Offset 1/3                                                                          | Herringbone                                                                         |



| Technical Information                 |                                                                              |
|---------------------------------------|------------------------------------------------------------------------------|
| Product                               | Metrik Slab                                                                  |
| Standard                              | CSA A231.1                                                                   |
| Flexural Strength                     | ±4.5 MPa                                                                     |
| Compressive Strength                  | N/A                                                                          |
| De-icing salts freeze-thaw durability | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles |
| Density                               | N/A                                                                          |
| Absorption                            | N/A                                                                          |
| Dimension Tolerance*                  | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm         |

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.