

Mondrian® Plus 80 Paver


	Metric (mm)	Imperial (in.)
A	80 x 165 x 330	3 1/8 x 6 1/2 x 13
B	80 x 330 x 330	3 1/8 x 13 x 13
C	80 x 330 x 495	3 1/8 x 13 x 19 1/2
Weight/unit (avg.)	17 kg	38 lb
Unit/area (avg.)	9.17 units/m ²	0.85 unit/ft ²
Area/layer	0.98 m ²	10.55 ft ²
Area/cube	8.82 m ² 9 Rows	94.95 ft ²
Qty/cube	A = 36 B = 36 C = 18	
Length/row	2.97 lin. m	9.75 lin. ft
Length/cube	26.73 lin. m	87.75 lin. ft
Weight/cube	1563 kg	3445 lb

Code	Colour - Prestige
10551159	Range Margaux Beige
10550461	Range Scandina Grey
Colour - Standard	
10551156	Range Norvick Grey
10551160	Range Newport Grey


Production location Milton
Can be double stacked

1 bag of Techniseal sand covers approx.: 49 ft²


Typical Row




Laying Pattern



Linear
100% Mix A, B, C



Modular
100% Mix A, B, C



Modular
100% Mix A, B, C



Technical Information

Product	Mondrian Plus 80 Paver
Standard	CSA A231.2
Flexural Strength	N/A
Compressive Strength	μ 50 MPa ≥ 45 MPa
De-icing salts freeze-thaw durability	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm
Runoff coefficient:	126 in. per hour

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).