


Brooklyn Paver





	Metric (mm)	Imperial (in.)
	60 x 230 x 76	2 3/8 x 9 x 3
Weight/unit	2.3 kg	5.1 lb
Unit/area	0.02 m²	0.188 ft²
Area/layer	0.96 m²	10.3 ft²
Area/cube	9.58 m² 10 Rows	103.13 ft²
Qty/cube	550 units	550 units
Weight/cube	1272 kg	2805 lb

Code	Colour - TrueColor
127002180	Midnight 
127002181	Rosewood 

Production location	Montreal
---------------------	----------

1 bag of Techniseal sand covers approx.: 67 ft²

Typical Row


Laying Pattern	
	
Checkerboard	Running Bond
	
Offset 1/3	Herringbone



Technical Information	
Product	Brooklyn Paver
Standard	CSA A231.2
Flexural Strength	N/A
Compressive Strength	µ 50 MPa ≥ 45 MPa
De-icing salts freeze-thaw durability	225 g/m² after 28 cycles 500 g/m² after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.