

# Lafitt® Plus Capping and Step

| Capping      | Metric (mm)        | Imperial (in.)       |
|--------------|--------------------|----------------------|
|              | 90 x 305 x 400     | 3 9/16 x 12 x 15 3/4 |
| Weight/unit  | 26.97 kg           | 59.4 lb              |
| Units/length | 2.50 units/lin. m  | 0.76 unit/lin. ft    |
| Length/row   | 2.40 lin. m        | 7.88 lin. ft         |
| Length/cube  | 21.60 lin. m       | 70.88 lin. ft        |
| Qty/cube     | 54 units    9 Rows | 54 units             |
| Weight/cube  | 1456 kg            | 3210 lb              |

| Code     | Colour              |
|----------|---------------------|
| 16253731 | Range Margaux Beige |
| 16253724 | Range Newport Grey  |
| 16253722 | Range Scandina Grey |
| 16253723 | Rockland Black      |


|                       |          |
|-----------------------|----------|
| Production location   | Metcalfe |
| Can be double stacked |          |
| Sold in full cubes    |          |

| Step        | Metric (mm)        | Imperial (in.)           |
|-------------|--------------------|--------------------------|
|             | 90 x 400 x 400     | 3 9/16 x 15 3/4 x 15 3/4 |
| Weight/unit | 35.69 kg           | 78.6 lb                  |
| Length/cube | 14.40 lin. m       | 47.25 lin. ft            |
| Qty/cube    | 36 units    9 Rows | 36 units                 |
| Weight/cube | 1285 kg            | 2830 lb                  |


| Code     | Colour              |
|----------|---------------------|
| 16253704 | Range Margaux Beige |
| 16253703 | Range Newport Grey  |
| 16253702 | Rockland Black      |
| 16253701 | Range Scandina Grey |

|                       |          |
|-----------------------|----------|
| Production location   | Metcalfe |
| Can be double stacked |          |
| Sold in full cubes    |          |

## Typical Row



## Typical Row



## Technical Information

|                                       |                                                      |
|---------------------------------------|------------------------------------------------------|
| Product                               | Lafitt Plus Capping                                  |
| Standard                              | ASTM C 1372                                          |
| Flexural Strength                     | N/A                                                  |
| Compressive Strength                  | 20.7 MPa                                             |
| De-icing salts freeze-thaw durability | N/A                                                  |
| Density                               | 2000 kg/m <sup>2</sup>                               |
| Absorption                            | 10.4%                                                |
| Dimension Tolerance*                  | Length: ±3.2 mm<br>Width: ±3.2 mm<br>Height: ±3.2 mm |



## Technical Information

|                                       |                                                              |
|---------------------------------------|--------------------------------------------------------------|
| Product                               | Lafitt Plus Step                                             |
| Standard                              | N/A                                                          |
| Flexural Strength                     | N/A                                                          |
| Compressive Strength                  | 35 MPa                                                       |
| De-icing salts freeze-thaw durability | 500 g/m <sup>2</sup>                                         |
| Density                               | 2250 kg/m <sup>2</sup>                                       |
| Absorption                            | 5%                                                           |
| Dimension Tolerance*                  | Length: ±2.0 mm<br>Width: ±2.0 mm<br>Height: -2.0 to +1.0 mm |



Additional details: See our landscaping installation guide on our website.