

Melville® 60 Small Rectangle Paver


| | Metric (mm) | Imperial (in.) |
|-------------|------------------------------|----------------------------|
| | 60 x 190 x 380 | 2 3/8 x 7 1/2 x 15 |
| Weight/unit | 10 kg | 22 lb |
| Area/unit | 13.89 units/m ² | 1.29 units/ft ² |
| Area/layer | 0.87 m ² | 9.33 ft ² |
| Area/cube | 10.44 m ² 12 Rows | 111.96 ft ² |
| Length/row | 4.57 lin. m | 15.00 lin. ft |
| Length/cube | 54.86 lin. m | 180.00 lin. ft |
| Qty/cube | 144 units | 144 units |
| Weight/cube | 1431 kg | 3154 lb |

| Code | Colour - Prestige |
|-------------------|---------------------|
| 12053044 | Range Amber Beige |
| 12052446 | Rockland Black |
| 12052448 | Range Scandina Grey |
| Colour - Standard | |
| 12053043 | Range Shaded Grey |


Production location Montreal, Quebec and Metcalfe
 Can be double stacked
 Sold in full cubes

1 bag of Techniseal sand covers approx.: 147 ft²


Typical Row



Laying Pattern



Linear



Herringbone



Technical Information

| | |
|---------------------------------------|--|
| Product | Melville 60 Small Rectangle Paver |
| Standard | CSA A231.2 |
| Flexural Strength | N/A |
| Compressive Strength | μ 50 MPa ≥ 45 MPa |
| De-icing salts freeze-thaw durability | 225 g/m ² after 28 cycles 500 g/m ² after 49 cycles |
| Density | N/A |
| Absorption | N/A |
| Dimension Tolerance* | Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm |

Sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. The Melville 60 Slab is compatible with the Melville 60 small rectangle paver for non-vehicular application only.