

Standard	Metric (mm)	Imperial (in.)
	150 x 300 x 200	5 29/32 x 11 13/16 x 7 7/8
Weight/unit	20.4 kg	45 lb
Unit/area	-	3.10 unit/ft ²
Area/cube	-	19.40 ft ²
Length/cube	-	39.40 lin. ft
Qty/cube	60 units	60 units
Weight/cube	1224 kg	2698 lb

Code	Colour
16259289	Grey
16259288	Granite Blend
16251887	Sierra Black


Production location Cambridge
 Can be double stacked
 Sold by 15 pieces

Corner	Metric (mm)	Imperial (in.)
	150 x 300 x 200	5 29/32 x 11 13/16 x 7 7/8
Weight/unit	20.94 kg	46.20 lb
Area/unit	-	0.81 ft ²
Qty/cube	36 units	36 units
Weight/cube	754 kg	1664 lb


Code	Colour
16259283	Grey
16259282	Granite Blend
16251886	Sierra Black

Production location Cambridge
 Can be double stacked
 Sold by piece


Typical Row



Typical Row



Laying Pattern



Linear



Technical Information

Product	RB Wall
Standard	ASTM C 1372
Flexural Strength	N/A
Compressive Strength	20.7 MPa
De-icing salts freeze-thaw durability	N/A
Density	2000 kg/m ²
Absorption	10.4%
Dimension Tolerance*	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

Applications: Retaining walls MAX 1.0 m (3.3 ft). Steps. Additional details: See our landscaping installation guide on our website.
Features: Most RB Wall component units come split. Corner units are sold as single, pre-split units.
Tips: Build vertical walls by knocking off back half of each of the two ribs on top of the block using a hammer and chisel.


RB 24 inch Wall Capping

Available in Ottawa and Gatineau only

Pre-Split	Metric (mm)	Imperial (in.)
	75 x 300 x 610	2 15/16 x 11 7/8 x 24
Weight/unit	29.75 kg	65.56 lb
Unit/area	-	2.00 units/ft ²
Length/cube	-	64.0 lin. ft
Qty/cube	32 units 4 Rows	32 units
Weight/unit	952 kg	2098 lb

Code	Colour
16251369	Grey
16251368	Granite Blend
16251874	Sierra Black

Production location	Cambridge
Can be double stacked	
Sold by layer (8 units)	



Technical Information

Product	RB 24-inch Wall Capping
Standard	ASTM C 1372
Flexural Strength	N/A
Compressive Strength	20.7 MPa
De-icing salts freeze-thaw durability	N/A
Density	2000 kg/m ²
Absorption	10.4%
Dimension Tolerance*	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

Additional details: See our landscaping installation guide on our website.