

# Rosebel® Slab


	Metric (mm)	Imperial (in.)
A	60 x 389 x 560	2 3/8 x 15 5/16 x 22
B	60 x 389 x 756	2 3/8 x 15 5/16 x 29 3/4
Weight/unit (avg.)	25 kg	54 lb
Area/unit (avg.)	0.18 m <sup>2</sup>	1.98 ft <sup>2</sup>
Area/layer	0.73 m <sup>2</sup>	7.90 ft <sup>2</sup>
Area/cube	8.76 m <sup>2</sup>	12 Rows 94.80 ft <sup>2</sup>
Qty/cube	48 units	48 units
Weight/cube	1180 kg	2601 lb

Code	Colour - Prestige
10200631	Range Margaux Beige
10200632	Range Amboise Beige
Colour - Standard	
10200633	Range Newport Grey
10200678	Range Norvick Grey


Production location	Quebec and Metcalfe
Can be double stacked	

1 bag of Techniseal sand covers approx.: 87 ft<sup>2</sup>

## Typical Row



## Laying Pattern



## Technical Information

Product	Rosebel Slab
Standard	CSA A231.1
Flexural Strength	±4.5 MPa
Compressive Strength	N/A
De-icing salts freeze-thaw durability	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm