

Boulevard TLI 150 Paver



Heavy Commercial

Colour - Smooth

White - Smooth

Cinder Grey - Smooth

Charcoal - Smooth

Black ETX - Smooth

Light Grey - Smooth

Beige Grey - Smooth

Beige - Smooth

Red - Smooth

Brown - Smooth

Colour - Textured

White - Granitech

Cinder Grey - Granitech

Charcoal - Granitech

Black ETX - Granitech

Light Grey - Granitech

Beige Grey - Granitech


Beige - Granitech

Red - Granitech

Brown - Granitech

200 x 200	Metric (mm)	Imperial (in.)
	150 x 200 x 200	5 7/8 x 7 7/8 x 7 7/8
Cube/ft ³	51.6	8.6 per row
Mass/ft ²	32.6 kg	71.7 lb
Sold separately		

Typical Row



Technical Information

Product	Boulevard TLI 150 Paver
Standard	CSA A231.2
Flexural Strength	N/A
Compressive Strength	μ 50 MPa ≥ 45 MPa
De-icing salts freeze-thaw durability	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.