


Cassara® Verde Paver

| | Metric (mm) | Imperial (in.) |
|-------------|-----------------------------|---------------------------|
| | 80 x 300 x 450 | 3 1/8 x 11 13/16 x 17 3/4 |
| Weight/unit | 13 kg | 28 lb |
| Unit/area | 7.36 units/m ² | 0.68 unit/ft ² |
| Area/layer | 1.09 m ² | 11.72 ft ² |
| Area/cube | 10.9 m ² 10 Rows | 117.2 ft ² |
| Length/row | 3.6 lin. m | 11.81 lin. ft |
| Length/cube | 36 lin. m | 118.10 lin. ft |
| Qty/cube | 80 units | 80 units |
| Weight/cube | 1003 kg | 2213 lb |


| Code | Colour |
|----------|-------------------|
| 10303142 | Range Shaded Grey |

| | |
|---------------------|----------|
| Production location | Montreal |
|---------------------|----------|

Typical Row



Laying Pattern



Checkerboard



Technical Information

| | |
|---------------------------------------|--|
| Product | Cassara Verde Paver |
| Standard | CSA A231.2 |
| Flexural Strength | N/A |
| Compressive Strength | μ 50 MPa ≥ 45 MPa |
| De-icing salts freeze-thaw durability | 225 g/m ² after 28 cycles 500 g/m ² after 49 cycles |
| Density | N/A |
| Absorption | N/A |
| Dimension Tolerance* | Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm |

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Additional details: See our landscaping installation guide on our website.