




Esbelto® DuraFusion Paver

| | Metric (mm) | Imperial (in.) |
|--------------|----------------------------|---------------------------|
| | 80 x 305 x 610 | 3 1/8 x 12 x 24 |
| Weight/unit | 37 kg | 81 lb |
| Unit/area | 5.382 units/m ² | 0.50 unit/ft ² |
| Area/layer | 1.11 m ² | 12.00 ft ² |
| Area/cube | 8.88 m ² 8 Rows | 96.00 ft ² |
| Length/layer | 3.66 lin. m | 12.00 lin. ft |
| Length/cube | 29.26 lin. m | 96.00 lin. ft |
| Qty/cube | 48 units | 48 units |
| Weight/cube | 1764 kg | 3888 lb |

| Code | Colour - Durafusion |
|-----------|--|
| 127003273 | Amber  N |
| 127003119 | Newport  N |
| 127003086 | Scandina  N |


Production location Milton

1 bag of Techniseal sand covers approx.: 176 ft²


Typical Row




Laying Pattern




Checkerboard



Running Bond



Offset 1/3



Herringbone



Technical Information

| | |
|---------------------------------------|--|
| Product | Esbelto DuraFusion Paver |
| Standard | CSA A231.2 |
| Flexural Strength | N/A |
| Compressive Strength | μ 50 MPa ≥ 45 MPa |
| De-icing salts freeze-thaw durability | 225 g/m ² after 28 cycles 500 g/m ² after 49 cycles |
| Density | N/A |
| Absorption | N/A |
| Dimension Tolerance* | Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm |

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Given the weight of this paver, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation).