

# Metrik™ Slab


	Metric (mm)	Imperial (in.)
	60 x 70 x 280	2 3/8 x 2 3/4 x 11
Weight/unit	3 kg	6 lb
Area/unit	0.02 m <sup>2</sup>	0.21 ft <sup>2</sup>
Area/layer	0.92 m <sup>2</sup>	9.95 ft <sup>2</sup>
Area/cube	11.09 m <sup>2</sup> 12 Rows	119.40 ft <sup>2</sup>
Qty/cube	576 units	576 units
Weight/cube	1505 kg	3319 lb

Code	Colour - Prestige
10502882	Rockland Black
127000940	Range Scandina Grey


Production location Milton  
Can be double stacked

1 bag of Techniseal sand covers approx.: 85 ft<sup>2</sup>


## Typical Row




## Laying Pattern




Checkerboard



Offset 1/2



Offset 1/3



Herringbone



## Technical Information

Product	Metrik Slab
Standard	CSA A231.1
Flexural Strength	±4.5 MPa
Compressive Strength	N/A
De-icing salts freeze-thaw durability	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.