


Virage Paver

	Metric (mm)	Imperial (in.)
	80 x 300 x 300	3 1/8 x 11 7/8 x 11 7/8
Weight/unit (avg.)	16 kg	36 lb
Unit/area (avg.)	11.41 units/m ²	1.06 units/ft ²
Area/layer	1.05 m ²	11.32 ft ²
Area/cube	8.41 m ² 8 Rows	90.54 ft ²
Length/row	3.55 lin. m	11.65 lin. ft
Length/cube	28.42 lin. m	93.23 lin. ft
Weight/cube	1548 kg	3413 lb

Code	Colour - Prestige
10303063	Range Scandina Grey

Production location	Bolton
---------------------	--------

Typical Row



Laying Pattern



Beaded pattern



Circle pattern



Link pattern



Mosaic pattern



Random pattern



Wave pattern



Flower pattern



Clover pattern



Technical Information

Product	Virage Paver
Standard	CSA A231.2
Void Opening	47%
Flexural Strength	N/A
Compressive Strength	μ 50 MPa ≥ 45 MPa
De-icing salts freeze-thaw durability	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).