



# Boulevard Hexagon Paver Light Commercial

| Colour - Smooth      |
|----------------------|
| White - Smooth       |
| Cinder Grey - Smooth |
| Charcoal - Smooth    |
| Black ETX - Smooth   |
| Light Grey - Smooth  |
| Beige Grey - Smooth  |
| Beige - Smooth       |
| Red - Smooth         |
| Brown - Smooth       |


|                      | Metric (mm)                | Imperial (in.)             |
|----------------------|----------------------------|----------------------------|
|                      | 100 x 256 x 300            | 4 x 10 1/16 x 11 13/16     |
| Unit/area            | 13.23 units/m <sup>2</sup> | 1.23 units/ft <sup>2</sup> |
| Cube/ft <sup>3</sup> | 68.32                      | 9.76 per row               |
| Mass/ft <sup>3</sup> | 22.33 kg                   | 49.13 lb                   |
| Sold separately      |                            |                            |



## Laying Pattern



Checkerboard



| Technical Information                 |                                                                              |
|---------------------------------------|------------------------------------------------------------------------------|
| Product                               | Boulevard Hexagon Paver                                                      |
| Standard                              | CSA A231.2                                                                   |
| Flexural Strength                     | N/A                                                                          |
| Compressive Strength                  | μ 50 MPa<br>≥ 45 MPa                                                         |
| De-icing salts freeze-thaw durability | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles |
| Density                               | N/A                                                                          |
| Absorption                            | N/A                                                                          |
| Dimension Tolerance*                  | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm         |

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.