


Celtik® Wall

	Metric (mm)	Imperial (in.)
A	90 x 225 x 175	3 9/16 x 8 7/8 x 6 7/8
B	90 x 225 x 265	3 9/16 x 8 7/8 x 10 7/16
C	90 x 225 x 345	3 9/16 x 8 7/8 x 13 9/16
D	90 x 225 x 435	3 9/16 x 8 7/8 x 17 1/8
Weight/unit (avg.)	14 kg	31 lb
Area/layer (1 to 6)	0.45 m ²	4.89 ft ²
Area/cube	3.18 m ² 7 Rows	34.22 ft ²
Qty/cube	A = 28 B = 28 C = 28 D = 28	
Length/row (1 to 6)	4.88 lin. m	16.00 lin. ft
Length/cube	34.14 lin. m	11.00 lin. ft
Weight/cube	1590 kg	3505 lb
For each unit of 90 mm, 1 alignment pin is included		
Note: 1/4 layer = 1.22 ft ²		
1/8 layer = 0.61 ft ²		


Code	Colour
16252364	Range Sheffield Beige and Black
16252362	Range Norvick Grey

Production location	Trois-Rivières
---------------------	----------------

Typical Row



Laying Pattern



Linear



Technical Information

Product	Celtik Wall
Standard	ASTM C 1372
Flexural Strength	N/A
Compressive Strength	20.7 MPa
De-icing salts freeze-thaw durability	N/A
Density	2000 kg/m ³
Absorption	10.4%
Dimension Tolerance*	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

Applications: Retaining walls - steps
Recommended Capping units: Celtik Straight Capping unit
 Additional details: See our landscaping installation guide on our website.