

# Mega Melville® Paver

|              | Metric (mm)                | Imperial (in.)            |
|--------------|----------------------------|---------------------------|
|              | 80 x 570 x 950             | 3 1/8 x 22 7/16 x 37 3/8  |
| Weight/unit  | 101 kg                     | 222 lb                    |
| Unit/area    | 1.85 units/m <sup>2</sup>  | 0.17 unit/ft <sup>2</sup> |
| Area/layer   | 1.08 m <sup>2</sup>        | 11.66 ft <sup>2</sup>     |
| Area/cube    | 7.56 m <sup>2</sup> 7 Rows | 81.62 ft <sup>2</sup>     |
| Length/layer | 1.90 lin. m                | 6.23 lin. ft              |
| Length/cube  | 13.29 lin. m               | 43.60 lin. ft             |
| Qty/cube     | 14 units                   | 14 units                  |
| Weight/cube  | 1410 kg                    | 3109 lb                   |

| Code     | Colour - Prestige   |
|----------|---------------------|
| 10550530 | Range Amber Beige   |
| 10551112 | Range Margaux Beige |
| 10550464 | Range Chambord Grey |
| 10559045 | Range Scandina Grey |
| 10550531 | Rockland Black      |
|          | Colour - Standard   |
| 10550529 | Range Shaded Grey   |
| 10550534 | Range Newport Grey  |


Production location Montreal and Quebec

1 bag of Techniseal sand covers approx.: 309 ft<sup>2</sup>


## Typical Row



## Laying Pattern



Linear



Modular  
83% Melville 80  
17% Mega Melville



## Technical Information

|                                       |                                                                              |
|---------------------------------------|------------------------------------------------------------------------------|
| Product                               | Mega Melville Paver                                                          |
| Standard                              | CSA A231.2                                                                   |
| Flexural Strength                     | N/A                                                                          |
| Compressive Strength                  | μ 50 MPa<br>≥ 45 MPa                                                         |
| De-icing salts freeze-thaw durability | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles |
| Density                               | N/A                                                                          |
| Absorption                            | N/A                                                                          |
| Dimension Tolerance*                  | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm         |

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Given the weight of this paver, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation).