



# Melia DuraFusion Slab


	Metric (mm)	Imperial (in.)
A	60 x 226 x 457	2 3/8 x 9 x 18
B	60 x 457 x 457	2 3/8 x 18 x 18
C	60 x 457 x 686	2 3/8 x 18 x 27
Weight/unit (avg.)	29 kg	64 lb
Area/unit (avg.)	0.21 m <sup>2</sup>	2.25 ft <sup>2</sup>
Area/layer	1.05 m <sup>2</sup>	11.25 ft <sup>2</sup>
Area/cube	10.45 m <sup>2</sup> 10 Rows	112.5 ft <sup>2</sup>
Qty/cube	A = 20 B = 10 C = 20	
Weight/cube	1460 kg	3219 lb

Code	Colour - DuraFusion	
127003278	Amber	 N
127001899	Marbella	


Production location Milton

1 bag of Techniseal sand covers approx.: 265 ft<sup>2</sup>


## Typical Row



## Laying Pattern



Linear



Modular



## Technical Information

Product	Melia DuraFusion Slab
Standard	CSA A231.1
Flexural Strength	±4.5 MPa
Compressive Strength	N/A
De-icing salts freeze-thaw durability	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.