

Melville® Classic 80 Paver


	Metric (mm)	Imperial (in.)
	80 x 100 x 200	3 1/8 x 3 15/16 x 7 7/8
Weight/unit	2.7 kg	5.95 lb
Unit/area	50.00 unit/m ²	4.57 unit/ft ²
Area/layer	1.10 m ²	11.82 ft ²
Area/cube	8.80 m ² 10 Rows	94.50 ft ²
Length/row	11.00 lin. m	36.10 lin. ft
Length/cube	88.00 lin. m	288.80 lin. ft
Weight/cube	1166 kg	2570 lb

Colour	
12059204	Grey


Production location	Montreal
---------------------	----------

1 bag of Techniseal sand covers approx.: 65 ft²


Typical Row




Laying Pattern




Linear



Herringbone



Herringbone 45°



Parquet



Technical Information

Product	Melville Classic 80 Paver
Standard	CSA A231.2
Flexural Strength	N/A
Compressive Strength	μ 50 MPa ≥ 45 MPa
De-icing salts freeze-thaw durability	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.