

Paleo® Plus Paver

	Metric (mm)	Imperial (in.)
A	60 x 150 x 130	2 3/8 x 5 7/8 x 5 1/8
B	60 x 150 x 150	2 3/8 x 5 7/8 x 5 7/8
C	60 x 150 x 170	2 3/8 x 5 7/8 x 6 11/16
D	60 x 150 x 188	2 3/8 x 5 7/8 x 7 3/8
Unit/area (avg.)	40.40 units/m ²	3.75 units/ft ²
Area/layer	0.99 m ²	10.66 ft ²
Area/cube	11.89 m ² 12 Rows	127.89 ft ²
Qty/cube	480 units (A = 96 B = 96 C = 96 D = 192)	
Length/row	6.60 lin. m	21.65 lin. ft
Length/cube	79.20 lin. m	259.85 lin. ft
Weight/cube	1671 kg	3677 lb

Code	Colour
10079015	Range Bourbon Beige
10079016	Range Norvick Grey


Production location	Quebec
Can be double stacked	

1 bag of Techniseal sand covers approx.: 71 ft²

Typical Row

D	D	D	D	D	D	D	D
A	A	A	A	A	A	A	A
C	C	C	C	C	C	C	C
D	D	D	D	D	D	D	D
B	B	B	B	B	B	B	B

Laying Pattern



Linear



Technical Information

Product	Paleo Plus Paver
Standard	CSA A231.2
Flexural Strength	N/A
Compressive Strength	μ 50 MPa ≥ 45 MPa
De-icing salts freeze-thaw durability	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles
Density	N/A
Absorption	N/A
Dimension Tolerance*	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).